

# Stone Look

GLAZED PORCELAIN

BEST TILE® / BESTTILE.COM

# Breton

## COLORS, SIZES & AVAILABILITY

NOMINAL SIZE	FINISH	THICKNESS	GROUT JOINT	FRESH	BLOOM	STREET	GLOW	FRAME	BOARD
12 x 24 Rectified	Matte	9 mm	1/8"	✓	✓	✓	✓	✓	✓
12 x 24 Rectified	Polished	9 mm	1/8"	✓	✓	✓	✓	✓	✓
24 x 24 Rectified	Matte	9 mm	1/8"	✓	✓	✓	✓	✓	✓
24 x 24 Rectified	Polished	9 mm	1/8"	✓	✓	✓	✓	✓	✓
24 x 48 Rectified	Matte	9 mm	1/8"	⊖	⊖	⊖	⊖	⊖	⊖
24 x 48 Rectified	Polished	9 mm	1/8"	⊖	⊖	⊖	⊖	⊖	⊖
32 x 32 Rectified	Matte	9 mm	1/8"	⊖	⊖	⊖	⊖	⊖	⊖
48 x 48 Rectified	Matte	9 mm	1/8"	⊖	⊖	⊖	⊖	⊖	⊖
48 x 48 Rectified	Polished	9 mm	1/8"	⊖	⊖	⊖	⊖	⊖	⊖
2 x 2 Mosaic	Matte	9 mm	NA	✓	✓	✓	✓	✓	✓
Hexagon Mosaic	Matte	9 mm	NA	✓	✓	✓	✓	✓	✓

✓ Stock Item. ⊖ Non-Stock Item. Requires Extra Lead Time.

## TECH INFO

<b>ORIGIN:</b> Italy <b>SHADE VARIATION:</b> V2 - Slight Variation <b>WEAR RATING:</b> All colors in Matte: 5 - Walls + Residential / Commercial Floor Applications; Bloom/Fresh/Street Polished: 4 - Walls + Residential / Light Commercial Floor Applications; Glow Polished: 3 - Walls + Residential Floor Applications; Frame/Board Polished: 2 - Walls + Light Residential Floor Applications It is not recommended to stagger any tile longer than 15" more than 1/3 the length of the tile.	RECOMMENDED APPLICATIONS	R	LC	C
	FLOORS	●	+	+
	WALLS / BACKSPLASH	●	●	●
	POOL DECKING			
	EXTERNAL USE - FROST PROOF	*	*	

● Approved for this application. + Bloom, Fresh & Street in Polished approved for LC; All Matte approved for C.  
 \* Discuss proper installation method with your Sales Representative.

## TILE PERFORMANCE DATA

TECHNICAL FEATURE	NORMS	RESULTS
Water Absorption	ISO 10545-3	≤ 0.5 % (Matte)
Abrasion Resistance (Glazed)	ISO 10545-7	5 (Matte)
Breaking Strength	ISO 10545-4	≥ 35 N/mm <sup>2</sup>
Dynamic Coefficient of Friction Wet	Acu Test	≥ 0.42 (Matte)
Dimensions Range	ISO 10545-2	Conforms
Frost Resistance	ISO 10545-12	Frost Proof
Chemical Resistance - Household Chemicals	ISO 10545-13	Min. Class B
Thermal Shock Resistance	ISO 10545-9	Resists
Resistance to Stains	ISO 10545-14	Min. Class 3

Always inspect materials prior to installation. Always mix 2-3 cartons at a time while installing to ensure the best blend. All product images are representative only. Variation in color and shading is to be expected. Final selection should be made from actual tile samples.