

Subway Tile

GLAZED PORCELAIN

BEST TILE® / BESTTILE.COM

Martini

COLORS, SIZES & AVAILABILITY

NOMINAL SIZE	FINISH	THICKNESS	GROUT JOINT	DENIM	GREEN	MINT	TIFFANY	GREY	PURE WHITE	SAND	TERRACOTTA
				✓	✓	✓	✓	✓	✓	✓	✓
2 x 6	Matte	9 mm	3/16"	✓	✓	✓	✓	✓	✓	✓	✓
2 x 6	Glossy	9 mm	3/16"	✓	✓	✓	✓	✓	✓	✓	✓
2 x 6 Stripes	Glossy	9 mm	3/16"	✓	✓	✓	✓	✓	✓	✓	✓
.5 x 12 Quarter Round	Matte	9 mm	3/16"	✓	✓	✓	✓	✓	✓	✓	✓
.5 x 12 Quarter Round	Glossy	9 mm	3/16"	✓	✓	✓	✓	✓	✓	✓	✓

✓ Stock Item. ◻ Non-Stock Item. Requires Extra Lead Time.

TECH INFO

R = Residential, LC = Light Commercial, C = Commercial

SHADE VARIATION: V3 - Moderate Variation WEAR RATING: Stripes: 1 - Wall Applications Only; Denim / Green / Terracotta: 3 - Walls + Residential Floor Applications; Grey / Mint / Sand / Pure White / Tiffany: 4 - Walls + Residential / Light Commercial Floor Applications Layout and blend cartons prior to installation.	RECOMMENDED APPLICATIONS	R	LC	C
	FLOORS	●	+	
	WALLS / BACKSPLASH	●	●	●
	POOL DECKING			
	EXTERNAL USE - FROST PROOF			

● Approved for this application. + Grey, Mint, Sand, Pure White & Tiffany in Matte or Glossy approved for this application.

TILE PERFORMANCE DATA

TECHNICAL FEATURE	NORMS	RESULTS
Water Absorption	ISO 10545-3	≤ 0.5%
Abrasion Resistance (Glazed)	ISO 10545-7	3 / 4
Breaking Strength	ISO 10545-4	≥ 35 N/mm ²
Dynamic Coefficient of Friction	AcuTest	> 0.42 (Matte)
Dimensions Range	ISO 10545-2	Conforms
Frost Resistance	ISO 10545-12	Frost Proof
Chemical Resistance - Household Chemicals	ISO 10545-13	GA/GLA
Chemical Resistance - Low Concentration of Acids and Bases	ISO 10545-13	GA/GLA
Thermal Shock Resistance	ISO 10545-9	Resistant
Resistance to Stains	ISO 10545-14	Conforms
Crazing Resistance of Glazed Tiles	ISO 10545-11	Resistant

Always inspect materials prior to installation. Always mix 2-3 cartons at a time while installing to ensure the best blend. All product images are representative only. Variation in color and shading is to be expected. Final selection should be made from actual tile samples.