

Quartz Essence



COLORS, SIZES & AVAILABILITY							Κχ	0
	NOMINAL SIZE	FINISH	GROUT JOINT	BURN	FLAKE	NEST	ROC	WILD
	12 x 24 Rectified	Matte	1/8"	✓	/	✓	~	\checkmark
	4 x 24 Rectified	Matte	1/8"	✓	✓	✓	✓	✓
	2 x 2 Mosaic	Matte	NA	✓	V	✓	✓	✓
							l	

✓ Stock Item. Č

U Non-Stock Item. Requires Extra Lead Time.

TECH INFO

3 x 24 Bullnose

ORIGIN: Italy	RECOMMENDED APPLICATIONS	R	LC	С
SHADE VARIATION: Wild; V3 - Moderate Variation; All other colors; V2 - Slight Variation	FLOORS	•	•	•
WEAR RATING: 5 - Walls + Residential / Commercial Floor Applications	WALLS / BACKSPLASH	•	•	•
It is not recommended to stagger any tile longer than 15" more than 1/3 the length of the tile.	PO <mark>OL D</mark> ECKING	*	*	
with engal of the tite.	EXTERNAL USE - FROST PROOF	*	*	

^{• -} Approved for this application.

TILE PERFORMANCE DATA

TECHNICAL FEATURE	NORMS	RESULTS
Water Absorption	ISO 10545-3	≤ 0.1 %
Abrasion Resistance (Glazed)	ISO 10545-7	5
Dynamic Coefficient of Friction Wet	AcuTest	≥ 0.42
Dimensions Range	ISO 10545-2	Conforms
Frost Resistance	ISO 10545-12	Frost Proof
Chemical Resistance - Household Chemicals	ISO 10545-13	Resistant
Chemical Resista <mark>nce -</mark> Low Concentration of Acids and Bases	ISO 10545-13	Resistant
Thermal Shock Resistance	ISO 10545-9	Resistant
Resistance to Stains	ISO 10545-14	Cleanable

^{* -} Discuss proper installation method with your Sales Representative