

Blended Look

COLOR BODY • PORCELAIN

BEST TILE® / BESTTILE.COM

Stoneways

COLORS, SIZES & AVAILABILITY

NOMINAL SIZE	FINISH	THICKNESS	GROUT JOINT	FLIGHT	NIGHT	SKY	VELVET
6 x 24 Rectified	Matte	9 mm	1/8"	☺	☺	☺	☺
12 x 24 Rectified	Matte	9 mm	1/8"	☑	☑	☑	☑
2 x 2 Mosaic	Matte	9 mm	N/A	☑	☑	☑	☑
1.3 x 3.8 Herringbone Mosaic	Matte	9 mm	N/A	☺	☺	☺	☺
3 x 24 Bullnose	Matte	9 mm	1/8"	☑	☑	☑	☑
6 x 12 Cove Base	Matte	9 mm	1/8"	☺	☺	☺	☺

☑ Stock Item. ☺ Non-Stock Item. Requires Extra Lead Time.

TECH INFO

R = Residential, LC = Light Commercial, C = Commercial

ORIGIN: USA SHADE VARIATION: V3 - Moderate Variation WEAR RATING: Class 5 - Rated for all residential and commercial applications It is not recommended to stagger any tile longer than 15" more than 1/3 the length of the tile.	RECOMMENDED APPLICATIONS	R	LC	C
	FLOORS	●	●	●
	WALLS / BACKSPLASH	●	●	●
	POOL DECKING	*	*	*
	EXTERNAL USE - FROST PROOF	*	*	*

● Approved for this application. * Discuss proper installation method with your Sales Representative.

TILE PERFORMANCE DATA

TECHNICAL FEATURE	NORMS	RESULTS
Water Absorption	ASTM C373	≤ 0.5 %
Breaking Strength	ASTM C648	≥ 250 lbs
Dynamic Coefficient of Friction Wet	AcuTest	0.42
Thickness Dimension	ASTM C499	In accordance
Facial Dimension	ASTM C499	In accordance
Warping Diagonal	ASTM C485	In accordance
Wedging	ASTM C502	In accordance
Frost Resistance	ASTM C1026	Frost Proof
Scratch Hardness	MOHS	6

Always inspect materials prior to installation. Always mix 2-3 cartons at a time while installing to insure the best blend. All product images are representative only. Variation in color and shading is to be expected. Final selection should be made from actual tile samples.