


Studio

Ceramic/Porcelain




AVAILABLE SIZES



8x9



3x12



.625x12 matita

DESCRIPTION

Studio is an appealing Spanish tile series composed of Studio 3 ceramic tiles and Studio Hex porcelain tiles. With its irregular edge, Studio 3 ceramic wall tile offers a handmade ceramic tile look in a modern 3" x 12" subway tile size format. Suitable for backsplash or other wall tile projects, Studio 3 is available in matte and glossy finishes in three colors. Finish off any space with Studio Hex, an 8" x 9" hexagon porcelain floor tile available in five matte colors.

STUDIO HEX




black

grey

white

silver

taupe




STUDIO 3 GLOSSY

white

silver

taupe




STUDIO 3 MATTE

snow



silver

taupe



TECHNICAL INFORMATION

TILE SIZES

Nominal	Shape	Finish	Thickness	Availability
3 x 12 Rectified		Matte/ Polished	10 mm	✓
8 x 9 Hexagon		Matte	10 mm	✓

COORDINATING TRIM

Nominal	Shape	Finish	Thickness	Availability
.625 x 12 Matita		Matte/ Polished	10 mm	✓

✓ Stock Item. ⓧ Non-Stock Item. Requires Extra Lead Time.

PERFORMANCE DATA

Characteristic	Norms	Results
Water Absorption	ISO 10545-3	Studio 3: 16% Studio Hex: ≤ 0.50 %
Deep Abrasion	ISO 10545-6	Studio Hex: ≤ 130 mm ³
Abrasion Resistance (Glazed)	ISO 10545-7	Studio 3: 1 Studio Hex: 2/3/4
Breaking Strength	ISO 10545-4	Studio 3: 20-30 N/mm ² Studio Hex: ≥ 35-40 N/mm ²
Dynamic Coefficient of Friction Wet	AcuTest	Studio Hex: 0.68
Dimensions Range	ISO 10545-2	Studio Hex: Conforms
Frost Resistance	ISO 10545-12	Studio Hex: Frost Proof
Chemical Resistance - Household Chemicals	ISO 10545-13	Studio 3: GA
Chemical Resistance - Low Concentration of Acids and Bases	ISO 10545-13	Studio 3: GA
Thermal Shock Resistance	ISO 10545-9	Resistant
Resistance to Stains	ISO 10545-14	Class 5
Crazing Resistance of Glazed Tiles	ISO 10545-11	Studio 3: Resists

SHADE VARIATION



V2 - SLIGHT VARIATION
Clearly distinguishable differences in texture and/or pattern within similar colors.

WEAR CODE

Studio 3: 1 - Rated for wall applications only.

Studio Hex White/Silver/Taupe: 4 - Rated for all residential and light commercial applications

Studio Hex Grey: 3 - Rated for all residential applications

Studio Hex Black: 2 - Rated for light residential applications

APPLICATIONS

	RESIDENTIAL	LIGHT COMMERCIAL	COMMERCIAL
FLOORS	✗ (Studio Hex Black/ Grey)	✗ (Studio Hex White/Silver/ Taupe)	
WALLS / BACKSPLASH	✗	✗	✗
POOL DECKING			
EXTERNAL USE - FROST PROOF			

✗ - Has been approved for this application.

* - Discuss proper installation method with your Sales Representative.

NOTES

Minimum Grout Joint Recommendation: 3/16"

Always inspect materials prior to installation.

Always mix 2-3 cartons at a time while installing to insure the best blend.

All product images are representative only. Variation in color and shading is to be expected. Final selection should be made from actual tile samples.